Model FH-series • 10GPM • 1000PSI



he FH-series line of fire hose testers, offers testing pressures up to 1,000 PSI, with flow rates up to 10 GPM. Gas, Electric, and Diesel driven models, designed to safely test fire hose up to 6" in diameter. A large 2 & 1/2" swivel inlet aids in the ability to quickly fill and bleed the fire hoses through the large 1 & 1/2" heavy duty manifold, with independently controlled stainless steel ballvalves. NO WILD LINES - unique to the RICE Hydro line of fire hose testers, a ballvalve strategically placed on the inlet piping allows the user to fill with "LARGE VOLUME at LOW PRESSURE" and test with 'LOW VOLUME at HIGH PRESSURE', eliminating the elements that may cause wild lines. The FH-series hose testers, meet or exceed test standards set forth by the NFPA (1962.5) and the RMA. A safe. less costly and more efficient way to test your fire hose, keeping your pumper ready for action, where it should be!

- Five year full product warranty
- Two or Four Independently Controlled Outlets, 1 & 1/2"
 Stainless Steel Self-Cleaning Ball valves, with NST Couplings
- Stainless Steel Liquid-Filled Gauge Ensures Accurate Readings, with Less Flutter
- Rugged Roll Cage Construction Protects Pump From Damage



3500 Arrowhead Drive

Carson City

Nevada

89706

web site:

www.ricehydro.com

e-mail:

ricehydro@ricehydro.com

Phone:

(775) 885-1280

Fax:

(800) 998-7423

FIRE HOSE TESTER SERIES							
MODELS;	FH-3	EL-FHT	FH-5(B) (H)	FH5-E	FH4-E	FH2-(B) (H)	FH10-(B) (H)
PSI	500	500	1000	800	1000	1000	450
GPM	3	3	5	5	4	3.5	10
MTR/ENG	1HP ELEC	1HP ELEC	GAS	3HP ELEC	3HP ELEC	GAS	GAS
PUMP	PLUNGER	PLUNGER	PLUNGER	PLUNGER	PLUNGER	PLUNGER	PISTON
SHIP DIM	27X22X17	25X21X17	35X25X19	35X25X19	35X25X19	35X25X19	35X25X19
SHIP WGT	168	117	184	206	210	160	174
INLET	ALL UNITS COME WITH A 2 & 1/2" SWIVEL INLET ADAPTER						
OUTLET	ET UNITS HAVE EITHER 2 OR 4, 1 & 1/2" INDEPENDENTLY CONTROLLED NST OUTLETS						
OPTIONS: Motors - Standard units are equipped with 110/220V, totally enclosed fan cooled, overload protection, 50/60 Hertz readings							

Special order options include; Explosion proof, Phase and Voltage variations

1 HP at 110V, 3 HP at 220V, all others are per customer specifications

Engines - Honda, Briggs & Stratton, Robin, and Diesel

MINI HOSE TESTER

Model EL-FHT



he EL-FHT is a mini hose tester with all the power and design of the FH-3, yet just half its size. Great for on board ships, inside factories and plants or any confined spaces.

- Two Independently Controlled Outlets, 1 & 1/2" Stainless Steel **Ball valves, with NST Couplings**
- 1 HP 50/60 Hz Electric Motor with MTO, and TEFC
- Dual Swivel Inlets: 2 & 1/2" NST and 3/4"GHT.
- **Liquid Filled Stainless Steel Certified Gauge**

Model FH10-H

reedom and Versatility! The FH 10-H is one of six gas models offered in the Rice Hydro line of fire hose testers. Excellent for testing requirements in rural and remote areas, or anywhere electricity is not readily available.

- Shown with Honda engine, OHV, oil alert
- All units enclosed in a Rugged Steel Rollcage
- Increased speed and efficiency with higher GPM flow ratings





FH-series Wand Accessory



deal for Haz-Mat and contaminated

cleaning power at 500 psi, yet soft enough to offer less risk for damage of department decals or custom paint jobs. The FHWA-1 wand accessory makes your FH-seires fire hose tester a year HYDRO INC. round contributor to your equipment fleet.

- Dual Tips offer option of Spraying Either Water only or Soap & Water
- 50 Feet of High Pressure Hose for Long **Range Mobility**
- Quick Disconnects for Easy On/Off Capability
- Adjustable Injector for Soap or other **Cleaning Solvents**
- Steel Construction, with Nylon Tip Guards and Handle

