

PARTS BREAKDOWN FOR MODEL MTP'S  
RICE HYDRO, INC.

PART NUMBER..	DESCRIPTION..	QTY REQ'D
	MTP-5, MTP-1, MTP-15	
HAND-PUMP-BODY	BODY	1
	SPEC-01380	
	ORING-2-214	
PLUNGER	PLUNGER	1
BALLVALVE-3/8 (MTP-5)	OUTLET BALLVALVE	1
BALLVALVE-3/8HP (MTP-1 & MTP-15)	OUTLET BALLVALVE	1
CHECKVALVE-3/8-FM	3/8" FEMALE CHECKVALVE (INLET)	1
CHECKVALVE-3/8M	3/8" MALE CHECKVALVE (OUTLET)	1
SPEC-01380	O-RING	1
HOESWIVEL-1/2	1/2" X 3/4" HOSE SWIVEL	1
HOESCREEN&WASHER	3/4" HOESCREEN & WASHER	1
GRIPS-1"	BLACK GRIPS	1
TUBE-RND-1X.120	HANDLE	16.5
ORING-2-214	ORING	1
STEL-BRASS-3/8X90	3/8" X 90 BRASS ELBOW	1
NIP-RED-BR-1/2X3/8	1/2" X 3/8" BRASS REDUCING NIPPLE	1
TEE-BRASS-3/8	3/8" BRASS TEE	1
NIP-BRASS-3/8HEX	3/8" HEX BRASS NIPPLE	1
CLEVISPIN-1"	1" CLEVIS PIN	3
HOSE-1/4X5800K-8	1/4" OUTLET HOSE	1
GAUGE-600 (MTP-5)	600 PSI LIQUID FILLED	1
GAUGE-1500 (MTP-1)	1500 PSI LIQUID FILLED	1
GAUGE-2000 (MTP-15)	2000 PSI LIQUID FILLED	1

MTP's with tank reservoir

TANK-17X7X7	3 GALLON RESERVOIR TANK	1
TANK-CAP-ASSY	LOCKING CAP WITH CHAIN	1
HOSE-RECIRCUL-3/8	CLEARFORCE RECIRCULATING	11 IN.



WARNING: Operating, servicing and maintaining this equipment can expose you to chemicals including engine exhaust, carbon monoxide and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, operate and service your equipment in a well-ventilated area and wear gloves or wash your hands frequently when servicing your equipment. For more information go to: [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)